



## Approval continue

Boverket's Building Regulations (BBR) (BFS 2011:6 as amended up to and including BFS 2024:5) <sup>1</sup>:

Wastewater installations	6:641
Design	6:644
Fixtures, fittings and equipment	8:32

<sup>1</sup> May be applied to the extent stated in the transitional provisions of Boverket's regulations BFS 2024:14.

## Associated documents

Vieser One floor drain DN50 1x32 extra low, installation instructions marked 6004634/002/2022-02-15

## Control

The factory production control (FPC) is monitored by an independent inspection body.

Control plan: Vieser floor drain dated 2025-11-11. Inspection body: Eurofins

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval and associated documents. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.

## Manufacturing place

Production control includes the following place:

Vieser Oy, Keskutie 23, FI-61850 Kauhajoki as, Finland

## Marking

The product is to be marked at the factory. The marking consists of a text on every product and packing supplied and includes:

### On the packaging:

Holder	Vieser Oy
Manufacturing place	Vieser Oy, Kauhajoki, Finland
Product type designation	Vieser extra low floor drains
Type approval number	C900243
Boverket's registered trade mark	†
RISE Accreditation number	1002
Inspection body	Eurofins

### On the product:

Product type designation	Vieser extra low floor drains
Boverket's registered trade mark	†
Dimension	DN 50
Consecutive manufacture date of production	Year and month

## Basis for approval

Report VTT-S-01168-13 from VTT, Finland.

Reports EUFI29-18000169-T1, EUFI29-19003984-T1, EUFI29-20001414-T4 and EUFI29-24005099-T1 from Eurofins.

## Comments

Installation instructions shall be delivered with floor drain.

The floor drain has been judged to meet the requirements according to SS-EN 1253-1. The function of the partially mechanical water trap is judged to correspond to a water trap depth of 50 mm, the water trap should be cleaned regularly.

Associated documents shall accompany the product or by other means be available to users of the product.

This type approval supersedes the previous type approval with the same number dated 2022-05-30.

## Validity

Valid up to and including 2026-12-06.

The validity of this type approval can be verified at RISE homepage.

The validity of this type approval expires when the type approved product with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011 or 2024/3110.

A handwritten signature in blue ink, appearing to read 'Stefan Coric', is written over a light blue horizontal line.

Stefan Coric

*This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish original shall take precedence.*